



BLAZER LEP, LED, &  
Infrared Illuminators  
Light Shaping Diffusers  
Clamp & Retaining Ring  
Tools & ORING Tethers



#### Zip Bag Contents

1 pc Hot Spot & Spill (installed)  
3 pc Beam Diffusers (see list)  
1 pc Diffuser Retaining Ring  
1 pc Clamping Ring  
1 pc Retaining Ring Tool  
1 pc Hex Key Tool  
6 pc O-Ring Tethers



**Green Diffuser Works On  
White Lights ONLY -  
Not Infrared Illuminators**

Diffusers - 4x INCLUDED  
1 pc Flood 15°  
1 pc Flood, CQB 40°  
1 pc Hot Spot & Spill  
1 pc Green - Predator Hunt

## Installation Steps

1. The clamping & retaining rings have struts that must be aligned for o-ring attachment.
2. Make sure the bolt head (for hex key tightening) is on the right side, or left if you're a lefty.
3. Once aligned, connect the retaining ring and the clamping ring struts with the supplied o-ring tethers. (one, or two each side)
4. Now that both the clamping & retaining rings are tethered, back out the clamping ring bolt.
5. Slide the entire assembly over the light head.
6. Once the o-ring tethers are moderately taught, tighten the bolt to secure the clamping ring.
7. The assembly should be thumb "flippable" with relative ease - fine adjustments may be needed to dial in your preferred diffuser position.
8. Use the "half moon" retaining ring tool to switch out one of the 4x included beam diffusers - 15° & 40° Flood; Hot Spot & Spill; Green.
9. Diffusers have protective film covers to prevent damage. 15° = Yellow, 40° = White; Green = Clear.